

ALANIS ESD

0RE10114



DESCRIPTION

Alanis is a reliable **high-cut safety shoe** for those working in challenging conditions. The **Nabuk-effect microfiber upper** is **water-repellent** and **durable**, keeping feet dry and comfortable. Fitted with a **Fibertoe toe cap** and an ultra-light puncture-resistant insole, it ensures protection without adding unnecessary weight. The EVA + black rubber **outsole delivers** outstanding **wear resistance** and **stability** on slick surfaces. Completely **metal free**, Alanis is ideal for professionals who demand performance at the highest level.

UPPER

Water-repellent Nabuk-effect microfiber

LINING

Wingtex® air tunnel

TOECAP

FiberToe

ANTIPERFORATION

Ultra-light puncture-resistant insole

MIDSOLE

U-Power original

SOLE/TREAD

EVA + Black rubber

ANATOMICAL INSOLE

Natural Comfort 11 Mondopoint®

SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

FIBERTOE TOE CAP

Made from fibreglass to provide high mechanical resistance to impact and crushing. Weighing approximately 52 grams, it offers thermal insulation, flexibility and comfort, whilst keeping the footwear lightweight and safe.

PROTECTION CLASS

S3S CI HI HRO FO SR

EU NORM

EN ISO
20345:2022+A1:2024

SIZES

35-48 (UK: 2-13)

ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES

