

ATON ESD

0RE20016



DESCRIPTION

Aton is the ideal solution for those seeking protection, comfort, and lightness. Its **stretchy U-KNIT upper**, created with laser technology, **ensures** maximum **breathability** and **flexibility**. The **Fibertoe toe cap** protects the foot, while the **ultra-light puncture-resistant insole** delivers top-tier safety against perforation. The footwear is completely metal free. An **EVA and black rubber outsole** provides **grip** and **durability**, perfect for tackling challenging surfaces. Available in sizes 35 to 48, ideal for dynamic work environments.



UPPER

Stretch U-KNIT with laser processing

LINING

Wingtex® air tunnel

TOECAP

FiberToe

ANTIPERFORATION

Ultra-light puncture-resistant insole

MIDSOLE

U-Power original

SOLE/TREAD

EVA + Black rubber

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint®

SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

FIBERTOE TOE CAP

Made from fibreglass to provide high mechanical resistance to impact and crushing. Weighing approximately 52 grams, it offers thermal insulation, flexibility and comfort, whilst keeping the footwear lightweight and safe.

PROTECTION CLASS

S1PS HI HRO FO SR

EU NORM

EN ISO
20345:2022+A1:2024

SIZES

35-48 (UK: 2-13)

ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES

