



BLINK s ESD

0RL20334



DESCRIPTION

White Safety shoes low, light and comfortable U-Power of the Red Lion range, totally "metal free", with New safety dry upper, composite toecap, water-repellent, padded nylon bellows, anti-slip and PU / PU Infinergy® sole.

UPPER

Water repellent, breathable New Safety Dry

LINING

Wingtex® air tunnel

TOECAP

AirToe Composite

ANTIPERFORATION

Save & Flex® PLUS® , pierce resistant "non metal"

MIDSOLE

U-Power original

SOLE/TREAD

PU/PU and Infinergy®

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint

AIRTOE COMPOSITE TOECAP

A versatile solution made from a completely metal-free composite material. Weighing approximately 50 grams, it offers excellent thermal insulation and a lightweight design suitable for prolonged use in a variety of working environments.

SAVE & FLEX® PLUS

Save & Flex® PLUS anti-perforation insert. Textile, metal-free protective insert designed to provide superior lightness and flexibility compared to traditional steel plates. Sewn directly onto the upper, it ensures full-foot plantar protection. It offers sole penetration resistance up to 1100 N in compliance with current safety standards.

ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

INFINERGY®

Closed-cell expanded polyurethane cushioning insert designed to return energy with every step. Engineered to reduce muscle fatigue, it provides consistent energy return during both walking and prolonged work activities, ensuring high levels of comfort and long-lasting cushioning in all working conditions.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

PROTECTION CLASS

S3S CI FO SR

EU NORM

EN ISO 20345:2022

SIZES

35-48 (UK: 2-13)

TECHNOLOGIES

