



KORA s

0RL1E214



DESCRIPTION

High and comfortable safety shoe, of the Red Over/GORE-TEX® range by U-Power, highly abrasion-resistant PUTEK® PLUS upper and drummed natural nubuck, water-repellent, Gore-Tex lining, BOA® Fit System, Aluminium toe cap and PU/VIBRAM and Infinergy® sole.

UPPER

High abrasion resistant PUTEK® PLUS, water repellent and breathable with soft nubuck leather inserts

LINING

GORE-TEX Performance Membrane

TOECAP

AirToe Aluminium



ANTIPERFORATION

Save & Flex® PLUS , pierce resistant “non metal”

MIDSOLE

WOW GEL

SOLE/TREAD

PU/VIBRAM and Infinergy®

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint

GORE-TEX®

Thanks to the GORE-TEX® membrane, water stays out whilst sweat is wicked away, ensuring dry feet and optimal breathability in all working conditions. The technology also provides an effective barrier against the penetration of common chemicals, ensuring lasting protection and comfort throughout the day.

VIBRAM®

A world leader in the industry, Vibram® develops rubber soles designed to ensure grip, stability, durability and safety. The result of over 80 years of research and innovation, they combine advanced design and exclusive compounds to deliver high performance, comfort and reliability in any environment.

PROTECTION CLASS

S7S CI HI HRO FO SR

EU NORM

EN ISO 20345:2022

SIZES

38-48 (UK: 5-13)

PU TEK PLUS

A high-tech fabric exclusive to U-Group, offering high abrasion resistance and optimal flexibility. Designed for S3 safety footwear, it guarantees four times the breathability of standard PU Tek, as per ISO 20344:11 testing. It is a durable material that is completely PVC-free.

AIRTOE ALUMINIUM TOE CAP

Made from aluminium to combine lightness with protection, ensuring thermal and dynamic comfort for the foot. Weighing approximately 54 grams, it is designed to maintain high safety standards without adding weight to the footwear.

SAVE & FLEX® PLUS

Save & Flex® PLUS anti-perforation insert. Textile, metal-free protective insert designed to provide superior lightness and flexibility compared to traditional steel plates. Sewn directly onto the upper, it ensures full-foot plantar protection. It offers sole penetration resistance up to 1100 N in compliance with current safety standards.

BOA® FIT SYSTEM

BOA® Closure System. Fast-lacing technology that replaces traditional shoelaces with a micro-adjustable dial, lightweight stainless-steel laces, and low-friction guides. Designed to provide a precise, even, and customized fit with a simple turn, it ensures stability and safety throughout the working day. The system is resistant to impacts, mud, and wear, and allows the footwear to be removed quickly when needed.

INFINERGY®

Closed-cell expanded polyurethane cushioning insert designed to return energy with every step. Engineered to reduce muscle fatigue, it provides consistent energy return during both walking and prolonged work activities, ensuring high levels of comfort and long-lasting cushioning in all working conditions.

WOW GEL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound, featuring self-moulding properties to evenly distribute body weight pressure. The structure is combined with a soft anti-shock gel insert in the heel area, designed to absorb impacts and optimize walking comfort.

TECHNOLOGIES

