MICHAEL s

0UF20156



DESCRIPTION

Safety shoes low, light and comfortable U-Power of the Flat Out range, with in soft suede leather upper with ventilation holes, aluminum toecap, anti-puncture, anti-slip and PU / PUTR GRIP sole.

UPPER

Soft suede upper with ventilation

LINING

Wingtex® air tunnel

TOECAP

AirToe Aluminium

ANTIPERFORATION

Save & Flex® PLUS® , pierce resistant “non metal”

MIDSOLE

U-Power original



SOLE/TREAD

PU/PU TR transparent compact Antislip, antistatic and oil resistant

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint

AIRTOE ALUMINIUM TOE CAP

Made from aluminium to combine lightness with protection, ensuring thermal and dynamic comfort for the foot. Weighing approximately 54 grams, it is designed to maintain high safety standards without adding weight to the footwear.

PROTECTION CLASS

S1PS FO SR

EU NORM

EN ISO 20345:2022 SB S1 PS FO SR

SIZES

38-47 (UK: 5-12)

SAVE & FLEX® PLUS

Save & Flex® PLUS anti-perforation insert. Textile, metal-free protective insert designed to provide superior lightness and flexibility compared to traditional steel plates. Sewn directly onto the upper, it ensures full-foot plantar protection. It offers sole penetration resistance up to 1100 N in compliance with current safety standards.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES

COPYRIGHTS © U-POWER - DON'T WORRY... BE HAPPY! BY U-GROUP S.R.L.