

# OWEN ESD

0RE10134



## DESCRIPTION

The Owen **high work shoes** offer a unique blend of **comfort, style and protection**. The **Nabuk-effect microfiber upper** is **water-repellent** and durable, ideal for keeping feet dry in difficult conditions. A **Fibertoe toe cap** and **ultra-light puncture-resistant insole** guarantee reliable safety all day long. The **EVA + light blue rubber outsole adds** a distinctive touch while delivering **excellent grip on any surface**. Fully **metal free**, Owen is perfect for those who need high-cut shoes that combine functionality with modern design.



## UPPER

Water-repellent Nabuk-effect microfiber

## LINING

Wingtex® air tunnel

## TOECAP

FiberToe



## ANTIPERFORATION

Ultra-light puncture-resistant insole

## MIDSOLE

U-Power original

## SOLE/TREAD

EVA + Blue rubber

## ANATOMICAL INSOLE

Natural Comfort 11 Mondopoint®

## SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

## FIBERTOE TOE CAP

Made from fibreglass to provide high mechanical resistance to impact and crushing. Weighing approximately 52 grams, it offers thermal insulation, flexibility and comfort, whilst keeping the footwear lightweight and safe.

## PROTECTION CLASS

S3S CI HI HRO FO SR

## EU NORM

EN ISO

20345:2022+A1:2024

## SIZES

35-48 (UK: 2-13)

## ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

## U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

## TECHNOLOGIES

