

# SHADOW ESD

0RE20124



## DESCRIPTION

The **Shadow work shoe** provides comfort and protection with a sleek, functional design. Its **Nabuk-effect microfiber upper** is **water-repellent** and **durable**, perfect for long workdays. A **Fibertoe toe cap** safeguards your foot, while the ultra-light puncture-resistant insole ensures reliable protection against perforations. The EVA + black rubber **outsole offers excellent grip** and **stability** on any surface. Completely **metal free**, Shadow is designed for those seeking lightweight footwear without compromising on performance.



## UPPER

Water-repellent Nabuk-effect microfiber

## LINING

Wingtex® air tunnel

## TOECAP

FiberToe

## ANTIPERFORATION

Ultra-light puncture-resistant insole

## MIDSOLE

U-Power original

## SOLE/TREAD

EVA + Black rubber

## ANATOMICAL INSOLE

Natural Comfort 11 Mondopoint®

## SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

## FIBERTOE TOE CAP

Made from fibreglass to provide high mechanical resistance to impact and crushing. Weighing approximately 52 grams, it offers thermal insulation, flexibility and comfort, whilst keeping the footwear lightweight and safe.

## PROTECTION CLASS

S3S CI HI HRO FO SR

## EU NORM

EN ISO

20345:2022+A1:2024

## SIZES

35-48 (UK: 2-13)

## ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

## U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

## TECHNOLOGIES

