REACTOR

0UL20096



DESCRIPTION

Reactor features a soft suede upper with textile inserts. The 3D mesh lining ensures superior breathability and moisture wicking.
The AirToe® aluminum safety toe cap provides maximum protection with a streamlined shape. The footbed in soft polyurethane dynamic compound delivers all-day comfort and support. The direct-attach dual-density PU sole with Infinergy® midsole offers cushioning and energy return and is slip, oil, and abrasion resistant. Static Dissipative SD 35 rated. Available in charcoal/green, sizes 3.5–12, 13, 14, U-niversal Fit width.



UPPER

Soft suede upper with Nylon inserts

LINING

3D Mesh lining for superior breathability and moisture wicking

TOECAP

AirToe Aluminum, maximum protection with streamlined shape

ANTIPERFORATION

-

MIDSOLE

U-Power Original

SOLE/TREAD

PU/PU + Infinergy®

ANATOMICAL INSOLE

from 3.5-12,13,14 U-niversal Fit width

INFINERGY®

Closed-cell expanded polyurethane cushioning insert designed to return energy with every step. Engineered to reduce muscle fatigue, it provides consistent energy return during both walking and prolonged work activities, ensuring high levels of comfort and long-lasting cushioning in all working conditions.

PROTECTION CLASS

I/C SD35 SRO

EU NORM

ASTM F2413-24

SIZES

from 3.5 to 14

TECHNOLOGIES

COPYRIGHTS © U-POWER - DON'T WORRY... BE HAPPY! BY U-GROUP S.R.L.