U GROUP SRL
Via Borgomanero n° 1
28040 Paruzzaro (NO)

LEGAL DATA:
Tax Code and Reg.Imp.Novara: 02041920030
CCIAA Novara REA: 211799
VAT: IT02041920030
Export Code: No015724
Share Capital: 119.000 Iv

CONTACTS:
WEBSITE: www.u-power.ai/en-gb
EMAIL: info@u-power.it
TEL: +39 0322 53 94 01
FAX: +39 0322 23 00 01

REV.
20/10/2026

TECHNICAL SHEET

0UT20134 - JAX ESD

S3S CI LG FO SR
Natural Confort 11-12-13 Mondopoint
FiberToe
FOOTWEAR TYPE "A"
TEST REPORT SIZE 42
WEIGHT 1549g
SIZES 35-49 (UK: 2-13,5)

PRODUCT PHOTO



LINES

REDFIT

TECHNOLOGIES

BOA · ESD · Infinergy · Save&Flex plus · Fibertoe · Natural Confort 11 · Nickel Free

DESCRIPTION

U-Power **Jax safety shoes** are designed to combine safety, style and superior comfort. The soft **natural Nubuck leather upper ensures resistance** and **protection**, for a **modern look** in any work setting. The innovative **BOA® Fit System** allows you for a **quick**, **accurate** and **stable adjustment of the fit**, guaranteeing maximum comfort even during intense movements. The FiberToe toe cap protects your feet from knocks and impacts, while retaining lightness and practicality and the **Save & Flex® PLUS anti-perforation insole** prevents the risk of accidental punctures. The **PU/PU Infinergy® sole** returns energy while you walk, reducing fatigue and improving daily performance. With **three interchangeable insoles included in the pack**, these shoes allow you further personalise the fit for unique, tailored comfort. Available in sizes from 35 to 49, Jax shoes provide a versatile, safe solution that is always ready to tackle daily challenges at work.

TECHNICAL SPECIFICATIONS

TECHNICAL SPECIFICATIONS	NORM EN ISO	VALUE
	EN ISO 20345:2022+A1:2024	
SAFETY TOE CAP		
Impact resistance. Free heights after collision mm	≥14	**15,5**
Compressive strength. Free heights after compr. mm	≥14	**20,5**
ANTI-PERFORATION INSERT		
Puncture resistance	≥1100N	**Compliant**
ELECTRICAL RESISTANCE OF THE SHOE		
Measurement result	$<10^9$ohm	**Compliant**
UPPER DYNAMIC WATERPROOFING AFTER 60'		
Water absorption after 60'	≤30%	**4,5**
Water transmitted after 60'	≤0,2 gr	**0,00**
Permeability to water vapor mg/(cm^2 h)	≥0,8	**5,2**
Permeability coefficient mg/cm^2	≥15	**47,2**
VAMP LINING		
Permeability to water vapor mg/(cm^2 h)	≥2	**77,5**
Permeability coefficient mg/cm^2	≥20	**620,2**
Resistance to abrasion	12800/25600 cycles	**No hole**
SOLE WEAR		
Abrasion resistance (volume loss) mm^3	≤150	**0,96**
Resistance to sole / midsole detachment N/mm	≥3	**3,4**
Heel energy absorption J	≥20	**47**
SLIP RESISTANCE		
On ceramic with NaLS (forward heel 7°)	≥0,31	**0,42**
On ceramic with NaLS (backward heel 7°)	≥0,32	**0,41**
SR-Slip resistance on ceramic with glycerin (forward heel 7°)	≥0,19	**0,30**
SR-Slip resistance on ceramic with glycerin (backward heel 7°)	≥0,22	**0,34**