

	U GROUP SRL Via Borgomanero n° 1 28040 Paruzzaro (NO)	LEGAL DATA: Tax Code and Reg.Imp.Novara: 02041920030 CCIAA Novara REA: 211799 VAT: IT02041920030 Export Code: No015724 Share Capital: 119.000 Iv	CONTACTS: WEBSITE: www.u-power.ai/en-gb EMAIL: info@u-power.it TEL: +39 0322 53 94 01 FAX: +39 0322 23 00 01	REV. 31/07/2026	
TECHNICAL SHEET		PRODUCT PHOTO	LINES	TECHNOLOGIES	
OUT10114 - PEAK ESD S3S CI LG FO SR Natural Confort 11-12-13 Mondopoint FiberToe FOOTWEAR TYPE "B" TEST REPORT SIZE 42 WEIGHT 1723g SIZES 35-49 (UK: 2-13,5)					
DESCRIPTION		TECHNICAL SPECIFICATIONS		NORM EN ISO	VALUE
U-Power Peak safety shoes are designed to ensure comfort, safety and strength in the workplace. The upper is made of fine, water repellent, pull-up leather, that is soft and hard-wearing, with a sturdy TPU support heel, to ensure stability and protection even in the most difficult conditions. The FiberToe toe cap ensures maximum protection without foregoing lightness, while the Save & Flex® PLUS anti-perforation insole protects the foot against all risks of perforation plus flexibility and comfort throughout the working day. The PU/ PU Infinergy® sole provides excellent cushioning, impact absorption and a unique return of energy, thus reducing fatigue and improving posture. The three interchangeable U-Power original insoles add the finishing touch to this high-performance safety shoe, available in sizes 35 to 49.		SAFETY TOE CAP		EN ISO 20345:2022+A1:2024	
		Impact resistance. Free heights after collision mm		≥14	15,5
		Compressive strength. Free heights after compr. mm		≥14	20,5
		ANTI-PERFORATION INSERT			
		Puncture resistance		≥1100N	Compliant
		ELECTRICAL RESISTANCE OF THE SHOE			
		Measurement result		<10°ohm	Compliant
		UPPER DYNAMIC WATERPROOFING AFTER 60'			
		Water absorption after 60'		≤30%	3,7
		Water transmitted after 60'		≤0,2 gr	3,7
		Permeability to water vapor mg/(cm^2 h)		≥0,8	0,9
		Permeability coefficient mg/cm^2		≥15	16,9
		VAMP LINING			
		Permeability to water vapor mg/(cm^2 h)		≥2	77,5
		Permeability coefficient mg/cm^2		≥20	620,2
		Resistance to abrasion		12800/25600 cycles	No hole
		SOLE WEAR			
		Abrasion resistance (volume loss) mm^3		≤150	0,96
		Resistance to sole / midsole detachment N/mm		≥3	3,4
Heel energy absorption J		≥20	47		
SLIP RESISTANCE					
On ceramic with NaLS (forward heel 7°)		≥0,31	0,42		
On ceramic with NaLS (backward heel 7°)		≥0,32	0,41		
SR-Slip resistance on ceramic with glycerin (forward heel 7°)		≥0,19	0,30		
SR-Slip resistance on ceramic with glycerin (backward heel 7°)		≥0,22	0,34		