

# ADAK ESD

0RE20114



## DESCRIPTION

The **Adak shoe** combines **modern design** with **high-level performance** to ensure safety in any work environment. The **Nubuck-effect microfiber upper** is water-repellent and durable, **perfect for keeping the foot dry** and comfortable. The **Fibertoe toe cap** ensures constant protection, while the **ultra-lightweight anti-puncture footbed** prevents punctures without adding weight. The **EVA and black rubber outsole** provides excellent grip, ensuring **stability on any surface**. It is a **metal free** low-top shoe ideal for all professionals.

## UPPER

Microfiber Nubuck effect, water repellent

## LINING

Wingtex® breathable aria tunnel

## TOECAP

FiberToe



## ANTIPERFORATION

Ultra lightweight anti-puncture footbed

## MIDSOLE

U-Power original

## SOLE/TREAD

EVA + Black Rubber

## ANATOMICAL INSOLE

Natural Comfort 11 Mondopoint®

## SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

## FIBERTOE TOE CAP

Fibertoe toe cap. Made from fibreglass to provide high mechanical resistance to impact and crushing. Weighing approximately 52 grams, it offers thermal insulation, flexibility and comfort, whilst keeping the footwear lightweight and safe.

## PROTECTION CLASS

S3S CI HI HRO FO SR

## EU NORM

EN ISO

20345:2022+A1:2024

## SIZES

35-48

## ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

## U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

## TECHNOLOGIES

