

ALYX ESD

0RE20134



DESCRIPTION

Alyx is a **low-top safety shoe** designed to provide **comfort** and **safety** with a touch of style. The **Nubuck-effect microfiber upper** is **water-repellent** and wear-resistant, providing all-day protection and comfort. The **Fibertoe toe cap** protects the foot, while the **ultra-lightweight anti-puncture footbed** prevents puncture hazards. **Totally metal free**, Alyx provides a lighter fit all day long. The **EVA and blue rubber outsole** not only **provides excellent grip**, but also adds a modern, dynamic detail. It is the ideal choice for complex work environments.



UPPER

Microfiber Nubuck effect, water repellent

LINING

Wingtex® with breathable air tunnel

TOECAP

FiberToe

ANTIPERFORATION

Ultra lightweight anti-puncture footbed

MIDSOLE

U-Power original

SOLE/TREAD

EVA + Blue Rubber

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint

SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

FIBERTOE TOE CAP

Fibertoe toe cap. Made from fibreglass to provide high mechanical resistance to impact and crushing. Weighing approximately 52 grams, it offers thermal insulation, flexibility and comfort, whilst keeping the footwear lightweight and safe.

PROTECTION CLASS

S3S CI HI HRO FO SR

EU NORM

EN ISO
20345:2022+A1:2024

SIZES

35-48

ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES

