

AYRTON s

0UF20166



DESCRIPTION

Low-top, lightweight and comfortable U-Power Flat Out range/assortment safety shoes with soft suede upper with ultra light Nylon abrasion-resistant and breathable inserts, aluminum toe cap, anti-puncture, slip-resistant and PU/PUTR GRIP sole.

UPPER

Soft suede leather with ultra-ligh abrasion-resistant and breathable Nylon inserts

LINING

Wingtex® breathable aria tunnel

TOECAP

AirToe Aluminium

ANTIPERFORATION

Save & Flex® PLUS®, "no metal" textile anti-puncture footbed

MIDSOLE

U-Power original

SOLE/TREAD

PU/PU TR compact anti-abrasion, anti-oil, anti-slip and anti-static

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint

AIRTOE ALUMINIUM TOE CAP

Made from aluminium to combine lightness with protection, ensuring thermal and dynamic comfort for the foot. Weighing approximately 54 grams, it is designed to maintain high safety standards without adding weight to the footwear.

SAVE & FLEX® PLUS

Save & Flex® PLUS anti-perforation insert. Textile, metal-free protective insert designed to provide superior lightness and flexibility compared to traditional steel plates. Sewn directly onto the upper, it ensures full-foot plantar protection. It offers sole penetration resistance up to 1100 N in compliance with current safety standards.

PROTECTION CLASS

S1PS FO SR

EU NORM

EN ISO 20345:2022

SIZES

38-47

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES

