



DAVE s

0RL20524



DESCRIPTION

Work shoes low-top shoes with PU/Vibram soles, particularly suitable in all situations where special insulation of the bottom of the shoe from heat, cold and increased heat resistance of the sole is required. The soft, water-repellent pull-up leather upper and Kevlar® DuPont™ stitching ensure strength, durability and thermal insulation. The PU reinforcing toe cap and double yellow and black laces ensure sturdiness and tightness of the lacing. Protection is provided by the AirToe aluminum toe cap and the Save & Flex®PLUS "No Metal" Puncture resistance system. Safety footwear with slip-resistant, abrasion-resistant and oil-resistant soles. These safety shoes have an intersole with Infinergy® system and provide more than 55% energy return with each step. Foot health is ensured by the ultra-breathable Wingtex® air tunnel lining. Dave is suitable for use in wet and cold environments, for use and outdoors on treacherous surfaces and uneven terrain such as construction and building sites, road work and road maintenance, installations, port areas, agriculture and gardening.

UPPER

Water-repellent pull-up leather

LINING

Wingtex® breathable air tunnel

TOECAP

AirToe Aluminium

ANTIPERFORATION

Save & Flex® PLUS®, "no metal" textile anti-puncture footbed

MIDSOLE

U-Power original

SOLE/TREAD

PU/VIBRAM and Infinergy®

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint®

VIBRAM®

A world leader in the industry, Vibram® develops rubber soles designed to ensure grip, stability, durability and safety. The result of over 80 years of research and innovation, they combine advanced design and exclusive compounds to deliver high performance, comfort and reliability in any environment.

AIRTOE ALUMINIUM TOE CAP

Made from aluminium to combine lightness with protection, ensuring thermal and dynamic comfort for the foot. Weighing approximately 54 grams, it is designed to maintain high safety standards without adding weight to the footwear.

SAVE & FLEX® PLUS

Save & Flex® PLUS anti-perforation insert. Textile, metal-free protective insert designed to provide superior lightness and flexibility compared to traditional steel plates. Sewn directly onto the upper, it ensures full-foot plantar protection. It offers sole penetration resistance up to 1100 N in compliance with current safety standards.

INFINERGY®

Closed-cell expanded polyurethane cushioning insert designed to return energy with every step. Engineered to reduce muscle fatigue, it provides consistent energy return during both walking and prolonged work activities, ensuring high levels of comfort and long-lasting cushioning in all working conditions.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES



PROTECTION CLASS

S3S CI HI HRO FO SR

EU NORM

EN ISO 20345:2022

SIZES

38-48