



# PARKER s ESD

0RV10024



## DESCRIPTION

Ultra-lightweight anti-static safety footwear with soft microfiber Nubuck effect , water-repellent upper. High-top safety shoes with lightweight aluminum AirToe toe cap and next-generation PU compound outsole that is anti-abrasion , anti-oil , anti-slip and anti-static . Work shoes that are lighter thanks to the use of innovative materials to make the sole and the Puncture resistance system, which consists of an ultra-lightweight anti-puncture textile insole . The result is work shoes whose weight has been significantly reduced , without compromising safety, to the advantages of the worker's well-being. Highly breathable men's/women's work shoes with Wingtex® air tunnel lining and an anatomical , antibacterial U-Power Original anti-sweat insole . The sole's special protection from the cold (≤ 10 °C) make these safety shoes especially suitable for : electricians , carpenters , craftsmen , warehousemen , logistics and transportation sector.



### UPPER

Microfiber nubuck effect, water repellent

### LINING

Wingtex® breathable aria tunnel

### TOECAP

AirToe Aluminium

### ANTIPERFORATION

Save & Flex Air

### MIDSOLE

U-Power Original

### SOLE/TREAD

New generation PU compound anti-abrasion, anti-oil, anti-slip and anti-static

### ANATOMICAL INSOLE

Natural Confort 11 Mondopoint

### SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

### AIRTOE ALUMINIUM TOE CAP

Made from aluminium to combine lightness with protection, ensuring thermal and dynamic comfort for the foot. Weighing approximately 54 grams, it is designed to maintain high safety standards without adding weight to the footwear.

### ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

### U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

## TECHNOLOGIES



### PROTECTION CLASS

S3S CI FO SR

### EU NORM

EN ISO 20345:2022

### SIZES

35-48