

ROB ESD

ORT10164



DESCRIPTION

The ROB ESD are versatile safety shoes designed to provide safety, comfort and performance throughout the working day. With protection class S3S CI HI HRO FO SR, they offer protection against impact, puncture, cold, heat and slipping on difficult surfaces. The soft tumbled nubuck leather upper, combined with the breathable lining, ensures a comfortable and durable fit. The toe cap and anti-puncture offers strength whilst been lightweight, while the high-grip sole ensures stability on a variety of surfaces. Ideal for industry, assembly, logistics and automotive.



UPPER

Soft, tumbled grey Nubuck leather

LINING

Wingtex® with breathable aria tunnel

TOECAP

NanoFiber Toe Cap, ultralight, metal free.

ANTIPERFORATION

Ultra-lightweight anti-puncture footbed.

MIDSOLE

U-Power Original.

SOLE/TREAD

Black HRO rubber

ANATOMICAL INSOLE

Natural Confort 11 Mondopoint®

SAVE & FLEX AIR

Save & Flex Air anti-perforation insert. Ultra-lightweight (extralight) protective insert designed to effectively protect the foot from nails and sharp objects without adding extra weight to the footwear. It provides high safety standards, flexibility, and full-foot plantar coverage, enhancing dynamic comfort during movement.

NANOFIBER TOE

Made from nanofibre to ensure maximum protection whilst keeping the weight to a minimum. Weighing around 40 grams, it is the lightest option in the range, designed to optimise balance and reduce fatigue during prolonged use.

PROTECTION CLASS

S3S CI HI HRO FO SR

EU NORM

EN ISO
20345:2022+A1:2024

SIZES

35-48

ESD (ELECTROSTATIC DISCHARGE)

Technology designed to continuously dissipate electrostatic charges accumulated by the human body to the ground. Certified footwear complies with the requirements of the CEI EN 61340 standards for the protection of electronic components, making it suitable for use in EPA (Electrostatic Protected Area) environments during both production and handling of sensitive devices.

U-POWER ORIGINAL

Anatomical footbed with arch support structure made from a soft dynamic BASF compound. It features self-moulding properties designed to evenly distribute body weight pressure across the sole of the foot, reducing pressure points and optimizing dynamic comfort.

TECHNOLOGIES

